



## wi4 Mesh

# MWR7300

## Mesh Wireless Router • for MOTOMESH Quattro

The MWR7300 extends coverage and connectivity in a MOTOMESH Quattro network by meshing access points and users together.



**By allowing data and video to hop through one or more Mesh Wireless Router (MWR), MOTOMESH enables robust, non-line-of-sight communications between users and the network. Mesh Wireless Routers also act as reference points for position location of users and vehicles within the MOTOMESH network. The MWR7300 requires only a power connection to operate, as data is transmitted 100% wirelessly between nodes. Direct network connectivity can also be provided to collocated IP devices, like video cameras or sensors, via two, built-in, Ethernet ports.**

### Licensed 4.9GHz and Unlicensed 2.4GHz

The MWR7300 contains two standards compliant, 802.11 (Wi-Fi) radios and two of Motorola's widely acclaimed, Mobility Enabled Access (MEA) mobile broadband radios. One set of Wi-Fi and MEA radios operate in the unlicensed, 2.4GHz band and the other set operate in the licensed, 4.9GHz public safety band.

Public Safety, Public Works and Public Access can all be given separate and dedicated wireless broadband access due to MOTOMESH's multi-radio, multi-frequency architecture.

### Easy to Install and Deploy

Flexible mounting hardware enables the MWR to be mounted on utility poles, traffic signals, billboards, buildings, etc. Innovative weatherproof power and network connectors make reliable deployments quick and easy. MWRs automatically power up and integrate themselves into the MOTOMESH network, saving money and time.

### Fast and Accurate Position Location

Depending on network configuration, every MEA radio can provide position location information that does not require the use of GPS satellites. MEA location information can assist in the deployment of resources, creating a visual map of asset positions at an incident, or across an entire city. Location information is generated quickly and accurately.

### Multiple IP Address Support

The MWR features two high-speed Ethernet ports and supports a total of six IP addresses (three addresses per port). This allows a network of IP enabled devices to be directly addressed, accessed and managed over the MOTOMESH network. Additional devices can be supported by simply linking the connected devices through a NAT capable router.

### Network Management and Monitoring

MeshManager software allows the MWR7300 to be managed and upgraded over-the-air (OTA). The MeshManager application provides a single, comprehensive network management suite for controlling security policies, network provisioning, client administration and performance monitoring of all the components of a MOTOMESH network.

### A Total End-to-End Solution

Motorola's wireless broadband portfolio offers an array of access and backhaul technologies for complete end-to-end municipal wireless initiatives. Motorola wi4 Fixed Point-to-Multipoint and Point-to-Point solutions can provide reliable, high-capacity Internet backhaul links to Motorola mesh networks. MeshPlanner and MeshScanner enable detailed network planning and optimization capabilities. Additionally, Motorola's MOTOwi4 Ready Applications Ecosystem offers a wide range of validated solutions to generate immediate benefit from your wireless network.

## SPECIFICATION SHEET

MOTOMESH Quattro  
Four Radio Meshed WiFi Network  
with Mobility Enabled Access

### BENEFITS

- Best-in-class radio performance
- Reliable coverage
- Best-in-class throughput
- Robust security

### MOTOwi4

MOTOMESH Quattro is part of the MOTOwi4 family of broadband access technologies, a comprehensive platform of wireless broadband solutions, applications and services. Designed to complement and complete wireless networks, MOTOwi4 solutions address a broad range of applications across municipal, enterprise, and operator segments. The comprehensive MOTOwi4 portfolio creates a true end-to-end ecosystem of complementary products, services and solutions that provide high speed connectivity enabling a broad range of applications in fixed, nomadic, portable or mobile environments. Working together, wi4 Mesh solutions combined with other MOTOwi4 access technologies deliver ubiquitous, metro-wide (community-wide, campus-wide) wireless broadband coverage.

### WHY MOTOROLA

Motorola is uniquely positioned to address the wireless broadband market through the MOTOwi4 vision. Motorola has aligned its business units and roadmaps to provide a comprehensive, end-to-end solution covering all aspects of the broadband wireless access deployment. With our deep and extensive patent portfolio, over a decade of R&D investment, and our experience as a global supplier of broadband wireless access solutions, Motorola is primed to deliver its best in class wireless networks. Motorola is committed to leading the industry with end-to-end wi4 Mesh solutions addressing the full scope of the operator's deployment needs including access, core, devices, network management and services.

## MOTOMESH QUATTRO • MWR7300 RADIO CHARACTERISTICS

	2.4GHz	2.4GHz	4.9GHz	4.9GHz
	802.11b/g	MEA	802.11	MEA
<b>Output Power</b>	21 dBm	24 dBm	24 dBm	24 dBm
<b>RF Modulation</b>	CCK / OFDM	QDMA	OFDM	QDMA
<b>Operating Frequency (GHz)</b>	2.4 - 2.4835	2.4 - 2.4835	4.94 - 4.99	4.94 - 4.99
<b>Maximum Burst Data Rate</b>	54 Mbps	6 Mbps	18 Mbps	6 Mbps
<b>Spectrum Used</b>	20MHz	60MHz	10MHz	20MHz
<b>Antenna Type</b>	Omni, 8 dBi	Omni, 8 dBi	Omni, 11 dBi	Omni, 11 dBi
<b>Antenna Connector</b>	N-Type	N-Type	N-Type	N-Type
<b>Default System Configuration</b>	Standard	Software Key	Software Key	Software Key

### NETWORK

<b>Network Management Software</b>	MeshManager EMS on Linux OS or Windows 2003 Server via SNMPv1, SNMPv2c or secure SNMPv3 • Web Interface via HTTPS (SSL) • 802.11 and MOTOMESH MIBs
<b>Network Interface</b>	Two (2) weatherized 10/100 Mbps Ethernet (RJ-45) ports, with surge protection

### SECURITY

<b>Virtual Private Network (VPN)</b>	Supports FIPS-140-2 encryption (Motorola Multi-Net Mobility)
<b>Client Encryption Support Authentication</b>	For 802.11b/g only: WEP, AES, TKIP, WPA and WPA2 (802.11i) <b>MEA:</b> 802.1X (Infrastructure/Client and Client/Client) <b>802.11:</b> 802.1X (Infrastructure/Client)

### POWER

<b>Power Requirements</b>	90 to 264 VAC, 47 - 63Hz single phase
<b>Power Connector</b>	AC, NEMA 5-15 power cord • 6 ft (1.83m)
<b>Power Consumption</b>	30W to 35W (with Canopy PoE)

### PHYSICAL

<b>Dimensions</b>	7" x 8" x 10" (17.8cm x 20.3cm x 25.4cm)
<b>Weight</b>	12 lbs (5.4kg)
<b>Packaging</b>	NEMA 4 environmental enclosure for indoor or outdoor deployment
<b>Mounting</b>	3" (7.62cm) diameter post mounting

### ENVIRONMENTAL

<b>Temperature Range</b>	-35 to 55 °C
<b>Humidity</b>	0 to 100%, non-condensing
<b>General Certifications</b>	FCC Part 15 and 90, UL, CSA
<b>Safety Certifications</b>	UL / CSA

### AVAILABLE OPTIONS

<b>Mounting</b>	Lamp post mount bracket assembly
<b>Power</b>	AC photo cell power adapter
<b>DC Input</b>	IAP6300 with 5-14 VDC input



**MOTOROLA**

Motorola, Inc. [www.motorola.com/mesh](http://www.motorola.com/mesh)

The information presented herein is to the best of our knowledge true and accurate. No warranty or guarantee expressed or implied is made regarding the capacity, performance or suitability of any product. Product specifications subject to change without notice. MOTOwi4, MOTOMESH, MEA, MeshConnex, MeshManager, SecureMesh, Canopy and Hop-by-Hop Security are trademarks or registered trademarks of Motorola, Inc. MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their registered owners. © Motorola, Inc. 2007